



MRS-opaska przegubowa

Zakres zastosowania
Typ konstrukcji
Norma
Materiał
Ochrona powierzchni

do węży zwrotnych i ssących
opaska przegubowa
podobne do DIN 3017
stal
galwanizowana

Nazwa	Zakres mocowania (mm)	Szerokość taśmy (mm)
MRS 17-19	17-19	18,0
MRS 20-22	20-22	18,0
MRS 21-23	21-23	18,0
MRS 23-25	23-25	18,0
MRS 25-27	25-27	18,0
MRS 26-28	26-28	18,0
MRS 29-31	29-31	18,0
MRS 32-35	32-35	20,0
MRS 36-39	36-39	20,0
MRS 40-43	40-43	20,0
MRS 44-47	44-47	20,0
MRS 48-51	48-51	20,0
MRS 52-55	52-55	20,0
MRS 56-59	56-59	20,0
MRS 60-63	60-63	20,0
MRS 64-67	64-67	22,0
MRS 68-73	68-73	24,0
MRS 74-79	74-79	24,0
MRS 80-85	80-85	24,0
MRS 86-91	86-91	24,0
MRS 92-97	92-97	24,0
MRS 98-103	98-103	24,0
MRS 104-112	104-112	24,0
MRS 113-121	113-121	24,0
MRS 122-130	122-130	25,0
MRS 131-139	131-139	25,0
MRS 140-148	140-148	25,0
MRS 149-161	149-161	25,0

Nazwa	Zakres mocowania (mm)	Szerokość taśmy (mm)
MRS 162-174	162-174	25,0
MRS 175-187	175-187	25,0