



## 50020 - Złączka wtykowa prosta z gwintem zewnętrznym

**Materiał:**  
**Medium:**  
**Pierścień zaciskowy:**  
**Pierścień zabezpieczający:**  
**Uszczelka:**  
**Ciśnienie robocze:**  
**Temperatura robocza:**

Mosiądz niklowany  
 Sprężone powietrze, próżnia  
 Stal nierdzewna AISI 304  
 Technopolimer  
 NBR 70  
 max. 15 bar  
 -20°C do 80°C

Nazwa	Wąż	A	B	C	L	CH1	CH2
50020 3-M5	3	M5	4	8	19	8	2
50020 4-M5	4	M5	4	8	21	10	2
50020 4-1/8	4	1/8	6	13	20	10	3
50020 4-1/4	4	1/4	8	16	19,5	16	3
50020 5-M5	5	M5	4	8	23,5	12	2
50020 5-1/8	5	1/8	6	13	22	12	4
50020 6-M5	6	M5	4	10	24,5	13	2
50020 6-1/8	6	1/8	6	13	23,5	13	4
50020 6-1/4	6	1/4	8	16	23,5	13	4
50020 6-3/8	6	3/8	9	20	25	13	4
50020 6-1/2	6	1/2	10	25	27	13	4
50020 8-1/8	8	1/8	6	13	25	14	5
50020 8-1/4	8	1/4	8	16	23	14	6
50020 8-3/8	8	3/8	9	20	24	14	6
50020 8-1/2	8	1/2	10	25	26,5	14	6
50020 10-1/4	10	1/4	8	16	30,5	17	6
50020 10-3/8	10	3/8	9	20	27,5	17	8
50020 10-1/2	10	1/2	10	25	27	17	8
50020 12-1/4	12	1/4	8	16	34,5	20	6
50020 12-3/8	12	3/8	9	20	34	20	8
50020 12-1/2	12	1/2	10	25	31	22	10
50020 14-3/8	14	3/8	9	20	35	21	10
50020 14-1/2	14	1/2	10	25	32	22	10
50020 6-M12X1,25	6	M12x1,25	8	15	23,5	13	4
50020 6-M12X1,5	6	M12x1,5	8	15	23,5	13	4
50020 8-M12X1,5	8	M12x1,5	8	15	27,5	14	6

