



50550 - Złączka wtykowa kątowa obrotowa typu Banjo

Materiał:
Medium:
Pierścień zaciskowy:
Pierścień zabezpieczający:
Uszczelka:
Ciśnienie robocze:
Temperatura robocza:

Mosiądz niklowany
Sprężone powietrze, próżnia
Stal nierdzewna AISI 304
Technopolimer
NBR 70
max. 15 bar
-20°C do 80°C

Nazwa	L1 (mm)	L2 (mm)	D	Wąż	A	B	CH1
50550 3-M5	19	24,5	9,0	3	M5	5	-
50550 4-M5	19	24,5	9,0	4	M5	5	-
50550 4-1/8	21	27	14,0	4	1/8	6	5
50550 5-M5	20	24,5	9,0	5	M5	5	-
50550 5-1/8	21,5	27	14,0	5	1/8	6	5
50550 5-1/4	24,5	31,0	18,0	5	1/4	8	6
50550 6-M5	20,5	24,5	9,0	6	M5	5	-
50550 6-1/8	22,5	27	14,0	6	1/8	6	5
50550 6-1/4	25	31,0	18,0	6	1/4	8	6
50550 8-1/8	24	27	14,0	8	1/8	6	5
50550 8-3/8	28	35,5	21,0	8	3/8	9	7
50550 8-1/4	26	31,0	18,0	8	1/4	8	6
50550 10-1/4	29	31,0	18,0	10	1/4	8	6
50550 10-3/8	30,5	35,5	21,0	10	3/8	9	7
50550 12-3/8	32,5	35,5	21,0	12	3/8	9	7